

# TRANSFER PUMP FOR LIQUIDS

LIQUIPORT 100, 1.100



- ▶ **NEW** equipped with brushless DC Motor
- ▶ Improved service life
- ▶ With integrated overheating protection
- ▶ Simple and intuitive operation
- ▶ Self priming, can run dry
- ▶ Analog and impulse control (RC)
- ▶ Splashproof IP65
- ▶ Small footprint

## Fields of application

- Chemistry
- Synthetic organic chemistry
- Pharmacology
- Adhesives and glue
- Polymers & polymer coating
- Food technology research
- Detergents and solvents

## Hydraulic data

Type	Flow rate	Suction height	Max. pressure
LIQUIPORT 100	0.2–1.3 l/min	3 mWg	1 bar
LIQUIPORT 1.100	0.2–1.3 l/min	3 mWg	4 bar

## Chemical resistance

Code	Pump head	Diaphragm	Valves
KT	PP	PTFE covered	FFKM
TT	PVDF	PTFE covered	FFKM
FT	PTFE	PTFE covered	FFKM

## Functions

S - Version	RC - Version
<ul style="list-style-type: none"> <li>• Manual operation</li> </ul>	<ul style="list-style-type: none"> <li>• Manual operation</li> <li>• Analog control: 0–10 V from 0 to 100% (others on request)</li> <li>• Start/Stop through logic control (TTL)</li> <li>• Output signal fault alarm</li> <li>• Cable for external control included</li> </ul>

## Technical data

- Main supply 100–240 V / 50–60 Hz
- Ambient temperature allowed +5 to +40 °C
- Liquid temperature allowed +5 to +80 °C
- Maximum viscosity allowed 150 cSt
- Power consumption 12–16 W
- Protection class IP65
- Dimensions: 130 x 99 x 177 mm
- Weight: 0.8 kg
- Supply with barbed fittings: for tubing ID 8 mm

# ACCESSORIES

LIQUIPORT 100, 1.100

## Mounting plate

	<b>ID-Nr.</b>
for wall mounting	160473



## Standfitting

	<b>ID-Nr.</b>
	160474



## Footswitch

	<b>ID-Nr.</b>
for impulse start and stop	155872





**Wolflabs**

# Wolf Laboratories Limited

[www.wolflabs.co.uk](http://www.wolflabs.co.uk)

Tel: 01759 301142

Fax: 01759 301143

[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)



**Use the above details to contact us if this literature doesn't answer all your questions.**

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

