



# STARTER 300D

Portable DO product



## Convenient, fast and easy to use

😊 Ohaus STARTER series product family welcomes a new member — STARETER 300D, a portable Dissolved Oxygen(DO) meter. STARTER 300D offers you a multi-function meter with a Galvanic DO electrode for fast and easy measurement. STARTER 300D is manufactured at world class facilities under ISO 9001, and it meets industry CE requirements.



### Well organized display and intuitive software

- Electrode condition icon 😊 😞 shows you the electrode performance intuitively
- 30 sets of data memory
- Easy access to most recent calibration data
- One-touch conversion among ppm, mg/L and % to meet different requirement
- Auto/manual endpoint, ATC/MTC, auto self-diagnosis and error message alert, battery saving mode



### NO warm up needed

- No need to wait, galvanic DO electrode allows you to take measurement immediately without the typical 15 minutes to 4 hours wait
- STARTER 300D is easy-to-service and low-maintenance



# STARTER 300D *Portable DO product*



## Ergonomic and compact multi-function design

- IP54 protect from water and dust
- Built-in stand makes meter benchtop friendly
- Electrode clip can be attached on either side of the meter
- Integrated labeling area for quick owner identification
- Wrist strap gives additional security
- Compact keypad design makes it easy for on-hand operation

## Specifications

<b>Measurement Range</b>	%	0.0 to 199.9%; 200 to 400%
	mg/L	0.00 to 19.99; 20.0 to 45.0 mg/L
	ppm	0.00 to 19.99; 20.0 to 45.0 ppm
	Temp.	0 to 50 °C
<b>Measurement Resolution</b>	%	0.1%; 1%
	mg/L	0.01 mg/L; 0.1 mg/L
	ppm	0.01 ppm; 0.1 ppm
	Temp.	0.1 °C
<b>Barometric range</b>	mmHg	375 to 825 mmHg
	mbar	500 to 1100 mbar
	hPa	500 to 1100 hPa
<b>Barometric resolution</b>	mmHg	1 mmHg
	mbar	1 mbar
	hPa	1 hPa
<b>Accuracy</b>	± 1%; ± 0.3 °C	
<b>Salinity compensation</b>	0.0 to 50.0 ppt	
<b>Calibration</b>	1 or 2 points	
<b>Memory</b>	30 sets, last calibration data	
<b>Power</b>	4 x AAA, 250 hrs	
<b>Size/Weight</b>	90 W x 170 D x 35 H mm	
<b>Weight</b>	0.18kg	
<b>Display</b>	liquid crystal	
<b>IP rating</b>	IP54	
<b>Input</b>	BNC; Cinch (NTC 30 kΩ)	
<b>Materials</b>	ABS	

## Order Information:

### ST300D-B 30031656

- STARTER 300D portable DO meter
- IP54 sets
- Wrist strap
- Electrode Clip
- 4 AAA batteries

### ST300D 30031655

- STARTER 300D portable DO meter
- IP54 sets
- Wrist strap
- Electrode Clip
- 4 AAA batteries
- STDO11 galvanic DO electrode
- STTEMP30 temperature electrode

### STDO11 30031639

- 1.1m cable

### STTEMP30 83033970

- Temperature electrode (NTC30KΩ)

### Portable bag STARTER 30031635

- Portable bag for STARTER Portable meters



**OHAUS CORPORATION**  
7 Campus Drive  
Suite 310  
Parsippany, NJ 07054 USA

Tel: (973) 377-9000  
Fax: (973) 944-7177

*With offices worldwide*  
www.ohaus.com  
pH@ohaus.com

\* ISO 9001:2008  
Registered Quality Management System

EN\_30061691 © Copyright Ohaus Corporation



😊 Thank you for choosing Ohaus, it's the right measure.